



## CATEGORY

Upholstery

## PROPERTIES



## CONTENT

78% Vinyl - Phthalate Free face, 22% Polyester backing

## BACKING

Polyester

## FINISH

Soil & Stain Resistant Top Coat with Ink Resistant Technology

## WIDTH

54"

## WEIGHT

30 oz./linear yard

## SHOWN RAILOADED

No

## DIRECTIONAL

No

## ROLL LENGTH

30 yards

## BREAKING STRENGTH

Warp 101/Fill 93

## SEAM SLIPPAGE

Warp: 50/Fill: 50

## ABRASION RESISTANCE

Exceeds 100,000 Double Rubs (Wyzenbeek) Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.

## COLORFASTNESS TO CROCKING

Dry: Class 4 min/Wet: Class 4 min

## COLORFASTNESS TO LIGHT

300 hours

## APPLICATION

Indoor

## FLAMMABILITY

Passes Cal 117-2013; NFPA 260/UFAC Class 1; FMVSS 302; May comply with Cal. Tech. Bul. 133 when combined with appropriate components.

## CLEANING

CFC: Coated Fabrics Cleaning - When a spill/stain occurs wipe immediately with a clean dry cloth. Carefully remove the majority of the stain then follow the steps below.

Soap & Water - Remove ordinary dirt and smudges with a mild soap and water solution using a soft cloth or towel. Rinse with fresh water and wipe dry.

Non-abrasive Cleaners - If residue remains, use a straight application of the following cleaners: Fantastik or 409 and gently clean with a soft cloth. Rinse with fresh water and wipe dry.

Isopropyl Alcohol - More stubborn stains may be eliminated using a cotton cloth soaked in 70-91% isopropyl (rubbing) alcohol. Wipe without spreading stain to surrounding area. A second application should be applied with vigorous rubbing in a circular motion. For highly textured material, a soft brush is recommended to clean valleys and crevices. Rinse with fresh water and wipe dry.

BC: Bleach Cleanable - 1 parts bleach, 9 parts water = 10% bleach, 90% water solution. Do not clean / disinfect fabric for longer than 10 minutes using the 10% bleach solution. Always rinse promptly with clean water after applying the bleach solution. Failure to do so will void any and all warranties.

Additional cleaning details at [www.mayerfabrics.com](http://www.mayerfabrics.com)

**WARRANTY**

Standard Upholstery | '5' Five Year Warranty

---

**GREENGUARD**  
Certified